

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number  
**WO 2004/020340 A3**

(51) International Patent Classification<sup>7</sup>: **B01D 17/12,**  
F17D 3/00

[US/US]; 13205 Stoney Springs Drive, Chardon, OH  
44024 (US).

(21) International Application Number:  
PCT/US2003/026456

(74) Agent: **HLAVKA, John, R.**; Watts Hoffmann Co., L.P.A.,  
P.O. Box 99839, Cleveland, OH 44199-0839 (US).

(22) International Filing Date: 22 August 2003 (22.08.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/406,545 28 August 2002 (28.08.2002) US

(71) Applicant (*for all designated States except US*): **KI-  
NETICO INCORPORATED** [US/US]; 10845 Kinsman  
Road, Newbury, OH 44065 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **PARK, Stuart**

[Continued on next page]

(54) Title: FLUID TREATMENT SYSTEM



(57) Abstract: A control valve for a water treatment system which includes a turbine (110) rotatably mounted within a water receiving chamber. A nozzle assembly (122) defines first and second fluid paths, one of the flow paths may include a fluid pressure response valve element (320) for controlling fluid flow along the one path. The system also comprises a nozzle assembly (122') defining a throat (302') extending from an inlet and terminating in an arcuate outlet conforming to the periphery of the turbine. A plurality of spaced apart and angled vanes (404) are disposed in the throat.